

KNOT WHEELS STRINGER BEAD TWIST-CARBON STEEL WIRE OR STAINLESS STEE WIRE



Pferd Advance Brush offers a complete range of power brushes for industrial use including Wheel, End, Cup, Shaft mount and Tube brushes. Stringer Bead Knot Wheel brushes are manufactured with tightly twisted knots and narrow face widths. Designed for tough applications, such as cleaning welds between passes when joining pipe. Stringer bead knots are characterized by low flex, high impact brushing.

PART NO.	BRUSH DIAMETER	BORE	WIRE SIZE	NO.OF KNOTS	TRIM LENGTH	FACE WIDTH	MAX RPM
82186	4	5/8-11	0.020	32	3/4	3/16	20,000
82307SS	4	5/8-11	0.020	32	3/4	3/16	20,000
82194	4-1/2	5/8-11	0.020	32	1	3/16	20,000
82315SS	4-1/2	5/8-11	0.020	32	1	3/16	20,000
82483	4-7/8	5/8-11	0.020	48	3/4	3/16	15,000
82604SS	4-7/8	5/8-11	0.020	38	1-1/16	3/16	15,000
82487	6	5/8-11	0.020	48	1-1/8	3/16	12,500
82612SS	6	5/8-11	0.020	48	1-1/8	3/16	12,500
82494	6-7/8	5/8-11	0.020	56	1-1/8	3/16	9,000
82619SS	6-7/8	5/8-11	0.020	56	1-1/8	3/16	9,000

Note: Different bore size available on request

* SS= Stainless Steel wire

KNOT WHEELS FULL CABLE TWIST – CARBON STEEL OR STAINLESS STEEL WIRE



Full cable twist is more aggressive than standard knots, these brushes provide low flex, high impact cleaning action and are designed for the strongest applications.

PART NO.	BRUSH DIAMETER	BORE	WIRE SIZE	NO.OF KNOTS	TRIM LENGTH	FACE WIDTH	MAX RPM
82296SS	4	5/8-11	0.020	22	3/4	3/8	20,000
82474	5	5/8-11	0.023	22	3/4	3/8	15,000
82599SS	5	5/8-11	0.023	22	3/4	3/8	15,000
82477	6	5/8-11	0.023	22	1-1/4	1/2	9,000
82602SS	6	5/8-11	0.023	22	1-1/4	1/2	10,000

Note: Different bore size available on request

* SS= Stainless Steel wire

CUP BRUSHES, KNOT WIRE



Pferd Advance Cup Brushes are available in diameters from 2-3/4" up to 6" with options of internal or external thread bore. It comes in heat treated high carbon steel, wire, stainless steel, brass or bronze. Built for machine spindles and angle grinders. Pferd Advance Cup Brushes offer top performance in application ranging from light cleaning to heavy duty removal and deburring.

PART NO.	DIAMETER	BORE	WIRE SIZE	TRIM LENGTH	MAX RPM
82225	2-3/4	M10 X 1.5	0.020	7/8	14,000
82336SS	2-3/4	M10 X 1.5	0.020	7/8	14,000
82228	2-3/4	M10 X 1.25	0.020	7/8	14,000
82338SS	2-3/4	M10 X 1.25	0.020	7/8	14,000
82523	4	5/8 - 11	0.023	1-1/4	9,000
82648SS	4	5/8 - 11	0.023	1-1/4	9,000
82529	5	5/8 - 11	0.023	1-3/8	7,000
82652SS	5	5/8 - 11	0.023	1-3/8	7,000
82531	6	5/8 - 11	0.023	1-1/2	6,000
82654SS	6	5/8 - 11	0.023	1-1/2	6,000

*SS= Stainless Steel wire

CUP BRUSHES, CRIMPED WIRE



These cup brushes are excellent tools for general industrial usage. Made with crimped tempered wire, these brushes provide fast cutting action for the removal of light encrustations of scale, rust, paint or weld spatter.

PART NO	DIAMETER	BORE	WIRE SIZE	TRIM LENGTH	MAX RPM
82246	2-3/4	M10 X 1.5	0.014	7/8	14,000
82356SS	2-3/4	M10 X 1.5	0.014	7/8	14,000
82247	2-3/4	M10 X 1.25	0.014	7/8	14,000
82357SS	2-3/4	M10 X 1.25	0.014	7/8	14,000
82511	4	5/8 - 11	0.020	1-1/4	9,000
82635SS	4	5/8 - 11	0.020	1-1/4	9,000
82515	5	5/8 - 11	0.020	1-1/4	8,000
82637SS	5	5/8 - 11	0.020	1-1/4	8,000
82517	6	5/8 - 11	0.020	1-3/8	6,000
82638SS	6	5/8 - 11	0.020	1-3/8	6,000

*SS= Stainless Steel wire